



G304/2242



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road

Newport NP23 5TB  
South Wales  
NP10 8QQO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

## PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)


Signed

*Andrew*

Dated

9 June 2004

BEST AVAILABLE COPY



Patents Form 1/77

Patents Act 1977  
(Rule 16)

THE PATENT OFFICE

A

30 MAY 2003

Request for grant of a patent

(See the notes on the back of this form. You must also get an explanatory leaflet from the Patent Office to help you fill in this form)



1/77

30MAY03 E811103-1 D00859  
P01/7700 0.00-0312343.7

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

P1716

2. Patent application number

(The Patent Office will fill in this part)

30 MAY 2003

0312343.7

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Translift Engineering Limited  
Unit 22, Padgets Lane  
South Moons Moat  
Redditch, Worcestershire B98 0RB

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

7092083002

4. Title of the invention

FORK LIFT TRUCK

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Anthony Cundy & Co.  
1 Olton Bridge  
245 Warwick Road  
Solihull B92 7AH

Patents ADP number (if you know it)

00002188001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

Yes

## Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 7

Claim(s) 2

Abstract

Drawing(s) 6 + 6

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) 1

Request for substantive examination (*Patents Form 10/77*)

Any other documents  
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

Anthony Gundy & Co.

29/05/2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Peter Watts  
0121 708 0080

### Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

### Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

## Fork Lift Truck

The present invention relates to fork lift trucks of the kind designed for use in narrow aisles of warehouses and the like, where the truck is to deposit  
 5 loads in and remove loads from the face of a stack, in a direction transverse to the length of the aisle, that is at right angles to the face of the stack.

In order to maximise the storage area of a warehouse, it is desirable to make the aisles of the minimum width possible. The aisles must however  
 10 be wide enough to permit the manoeuvring of fork lift trucks to deposit a load in or remove a load from the stacks.

In order to improve the manoeuvrability of the fork lift trucks and thus reduce the aisle width, GB 2234214, the disclosure of which is incorporated  
 15 herein by reference thereto, discloses a fork lift truck with two parts that are pivoted together. The rear part comprises a truck body which carries the driver, propulsion unit and counterweights to balance loads carried by a lifting mechanism mounted on the front part. A pair of driven wheels are provided on the truck body and a pair of non-driven wheels are provided on  
 20 the front part, as close as possible to the load bearing part of the lift mechanism. The truck is steered by turning the front part relative to the truck body, about the pivot axis.

In order to permit loads to be deposited or removed from the stacks at right  
 25 angles to the aisles, the front part must be capable of being turned at  $90^{\circ}$  or more to the truck body. As the front wheels approach  $90^{\circ}$ , the drive from the rear wheels will cause the front wheels to slide sideways along the aisle, rather than steering the truck towards the position in the stack into which a load is to be deposited or from which a load is to be removed.

In order to overcome this problem, it has been proposed, for example as disclosed in GB 2263088 or GB 2255941, the disclosure of which is incorporated herein by reference thereto, to provide differential drive to the rear wheels, in order to produce a steering effect.

---

5 A more effective approach, as disclosed in GB 2265344 and EP 1201596, the disclosure of which is incorporated herein by reference thereto, has been to drive the front wheels, instead of or in addition to the rear wheels.

However in order to provide stability, it is necessary for the weight  
10 distribution in this type of lift truck to be very much to the rear of the truck. It is consequently necessary with front wheel drive systems of this type, to provide an articulated front axle to ensure that both front wheels remain in driving engagement with the floor, in spite of irregularities in the floor surface. This will generate further stability problems, particularly with  
15 elevated loads and in practice articulation of the front axle must be limited to provide a maximum upward and downward movement of each wheel, of about 25mm. Even when the front axle is articulated in this manner, wheel spin is liable to occur if there are variations in the floor surface in excess of 20mm in 1.5m, which is typical for a newly laid warehouse floor.

20 According to one aspect of the present invention, a fork lift truck comprises a truck body, a lift mechanism connected to the truck body by means of a vertically extending pivot and means for turning the lift mechanism relative to the truck body about said pivot, the truck body having a pair of rear  
25 ground engaging wheels mounted on transverse axes, the lifting mechanism having a single ground engaging front wheel mounted centrally on a transverse axis, the front wheel having drive means.

The present invention provides a front wheel drive fork lift truck which will  
30 overcome the steering problems associated with rear wheel drive trucks of this type. Furthermore as the single front wheel will always be in driving

engagement with the floor, irrespective of irregularities in the surface of the floor, there is no need for articulation of the front axle and the problems associated therewith.

5 The front wheel may be driven, for example by a hydraulic or electric motor. The motor is preferably coupled directly to the wheel and the motor or a gearbox associated therewith partially built into the wheel to reduce the bulk and minimise the width of the mechanism. The power source for the wheel motor and also for the steering mechanism by which the lifting mechanism  
10 is turned about the pivot and for the lifting mechanism itself, for example a hydraulic pump driven by an engine, an engine driven electrical generator or a battery pack, is housed in the truck body. The rear wheels may also be driven in addition to the front wheel.

15 In accordance with a preferred embodiment of the invention, the front wheel is mounted centrally on a transverse axis as far forward towards the load bearing part of the lifting mechanism as possible, in order to maximise the load bearing capability of the truck.

20 The invention is now described, by way of example only, with reference to the accompanying drawings, in which:-

Figure 1 is a perspective view of one embodiment of a fork lift truck in accordance with the present invention;

25

Figure 2 is a diagrammatic side elevation of the fork lift truck shown in figure 1;

Figures 3 to 5 are diagrammatic plan views of the fork lift truck shown in  
30 figure 1, at various stages of a manoeuvring operation; and

Figure 6 is a diagrammatic plan view of an alternative embodiment of the invention.

---

As illustrated in figures 1 and 2, a fork lift truck 10 comprises a truck body 12 and lifting mechanism 14.

---

The truck body 12 has a pair of rear wheels 16 mounted on a common axis, which is transverse to the longitudinal axis of the lift truck. The wheels 16 have solid tyres 18. The truck body provides a cabin 20 having a seat 22, steering controls 24, drive control pedals 26 and lifting controls 28. Means, for example, a battery pack or engine driven generator or hydraulic pump, for providing power to the various systems of the truck 10 are also mounted in the truck body 12, together with counter balance weights.

The lifting mechanism 14 comprises a telescopic mast 30 comprising several rails 32, which may be moved in telescopic manner. A fork carriage 34 is mounted on the mast 30 for movement longitudinally of the rails 32. A pair of load engaging forks 36 are provided on the fork carriage 34. Drive means (not shown), for example hydraulic motors or rams, or electric motors are provided for extending the mast and for moving the fork carriage. Furthermore, means, for example a hydraulic ram (not shown) may be provided for tilting the mast 30, backwards from the vertical, in conventional manner.

A single front wheel 40 is mounted on the lifting mechanism 14, on a fixed axle which is transverse to the longitudinal axis of the truck when in the straight ahead position. The front wheel 40 is mounted beneath the mast 30 centrally of the lifting mechanism 14 and as far forward towards the forks 36 as possible, without fouling loads mounted on the forks 36. The wheel 40 has a solid tyre 42.

An electric motor 44 is mounted coaxially of the wheel 40 and is coupled to the wheel 40 by means of a gearbox 46 which is built partially into the hub of the wheel 40, in order to reduce the overall width of the wheel 40/motor 44/gearbox 46 unit.

5

The lifting mechanism 14 is pivotally connected to an arm 50 which extends forwardly from the front of the truck body 12, by means of a vertical bearing tube assembly 52. A steering mechanism, for example a hydraulic or electric motor and gear or chain mechanism, or hydraulic rams (not shown), is provided for turning the lifting mechanism 14 relative to the truck body 12 under control of the steering control 24, in order to steer the fork lift truck 10.

Figures 3 to 5 show a typical manoeuvre required to deposit or remove a load in bay 62 of a stack 60. The fork lift truck 10 is driven along an aisle 64 between two stacks 60. With the lifting mechanism 14 in the straight ahead position, similar to that illustrated in figure 3. As the truck 10 approaches the bay 62, the truck 10 is manoeuvred by turning lifting mechanism 14, so that the truck body is close into the stack 60 but angled away from the bay 62, as illustrated in figure 3. The lifting mechanism 14 is then turned towards the bay 62, while the truck 10 is driven forward by motor 44, so that the forks 36 gradually move into the bay 62, as illustrated in figure 4. Eventually the forks 36 are disposed at right angles to the stack 60, as illustrated in figure 5. The truck 10 may then be driven by motor 44, while reducing the steering angle, so that the forks 36 enter the bay 62 at right angles to the stack, so that a load mounted thereon may be deposited in the bay 62 or a load may be removed from the bay 62.

The fork lift truck 10 is at its least stable position when the lifting mechanism 14 is positioned at  $90^\circ$  to the line X - X joining the points of contact of the front wheel 40 and inside rear wheel 16 with the ground. In



this position the load mounted on the forks 36 will produce a moment about the line X - X. In order to balance the load carried by the truck 10, the centre of gravity of the truck must be positioned as far rearwardly as possible, in order to maximise the distance y between the centre of gravity and line X - X.

As the lifting mechanism 14 is rotated and the truck 10 is driven by the motor 44, the speed of the inside rear wheel 16 will reduce with increasing steering angle, until when the point of intersection A of the axis of the front wheel 40 with the axis of the inside rear wheel 16 coincides with the point of contact of the inside rear wheel 16 with the ground, the inside rear wheel 16 will be stationary, the truck 10 pivoting about the inside rear wheel 16. When the steering angle increases beyond this point, the inside rear wheel 16 will rotate backwards.

15

While in the above embodiment only the front wheel 40 is driven, in an alternative embodiment, all three wheels 16,44 may be driven. When all three wheels 16,40 are driven, control means may be provided to control the speed of rotation of the rear wheels 16, so that when turning the outside rear wheel 16 will speed up, while the inside rear wheel 16 will slow down and reverse, when the steering angle is such that the point of intersection A is inside the inside rear wheel 16. Alternatively, the wheels may be connected to a power source, such that under the forces generated by the drive applied to the front wheel 40 and outside rear wheel 16, the inside rear wheel 16 will slow down and eventually reverse, when the steering angle increases sufficiently, the power to the inside rear wheel 16 being automatically diverted to the other wheels 16,40.

According to an alternative embodiment, as illustrated in figure 6, the front and rear wheels 16,40 are driven by hydraulic motors 70, the hydraulic motors 70 being built into the hubs of the wheels 16,40. Hydraulic fluid is supplied under pressure to the hydraulic motors 70 by means of a hydraulic

30

pump 72 mounted in the truck body 12. The hydraulic pump 72 is driven by an internal combustion engine 74 powered by a fuel gas. A valve block 76 is provided for varying the flow of hydraulic fluid to the motors 70 to control the speed thereof and direction of the motors the motors 70. Return fluid from the motors 70 is delivered via the valve block 76 to a reservoir 78, which is connected back to the pump 72. Flexible hydraulic pressure hoses 80 are provided in the hydraulic lines between the valve block 76 and motor 70 driving the front wheel 40, in order to permit pivoting of the lifting mechanism 14. Other systems of the fork lift truck 10, for example the steering, the mast extension means, lifting mechanism and means for tilting the mast, may also be powered by hydraulic fluid from the pump 72 via the valve block 76.

Various modifications may be made without departing from the invention. For example while in the embodiment described with reference to figures 1 to 5, an electric motor is used to drive the front wheel, a hydraulic motor or other suitable drive means may be used. Similarly, in the three wheel drive embodiment described with reference to figure 6, the hydraulic motors may be replaced by electric motors other suitable drive means.

The present invention is also applicable to pedestrian operated fork lift trucks in which the operator walks behind the truck.

**Claims**

1. A fork lift truck comprising a truck body, a lift mechanism connected to the truck body by means of a vertically extending pivot and means for turning the lift mechanism relative to the truck body about said pivot, the truck body having a pair of rear ground engaging wheels mounted on transverse axes, the lifting mechanism having a single ground engaging front wheel mounted centrally on a transverse axis, the front wheel having drive means.

10

2. A fork lift truck according to claim 1 in which the lifting mechanism may be pivoted to the truck body at a steering angle of  $90^{\circ}$  or more.

3. A fork lift truck according to claim 1 or 2 in which the front wheel is positioned forwardly of the pivot connection between the truck body and the lifting mechanism.

15

4. A fork lift truck according to any one of the preceding claims in which the front wheel is positioned as far forward as possible towards the load bearing part of the lifting mechanism.

20

5. A fork lift truck according to any one of the preceding claims in which the rear wheels are independently driven.

6. A fork lift truck according to claim 5 in which means is provided for the differential drive of the rear wheels.

25

7. A fork lift truck according to claim 5 in which the rear wheels are connected to a power source in a manner which will permit power to be diverted automatically from the rear inside wheel to one or more of the other wheels, as a function of the steering angle.

30

8. A fork lift truck according to any one of the preceding claims in which the wheels are driven independently by hydraulic or electric motors.

9. A fork lift truck according to claim 8 in which the motor is connected  
5 to the wheel by a gearbox.

10. A fork lift truck according to claim 8 or 9 in which the motor and/or gearbox is built partially into a hub of the wheel.

10 11. A fork lift truck according to any one of claims 8 to 10 in which the power for the motors is provided by an engine driven generator or hydraulic pump, or by a battery pack.

12. A fork lift truck according to claim 11 in which the engine is an  
15 internal combustion engine powered by fuel gas.

13 A fork lift truck substantially as described herein with reference to and as shown in figures 1 to 5 or figure 6 of the drawings.




Fig 1





Fig 2.



- 60 -

Fig 3




Fig 4.






Fig 5.




Fig 6.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**